KK® Family Overview Circuil Size Per Pin **Custom KK®** (all pitch sizes) Max Voltage (AWG) Wire Gauge (AWG) KK[®] Key Options Available: Versions Other Features Friction Lock - Vertical, Right Angle · Glow wire material - W-to-B (Wire to Board) 250V 18-30 AWG 5.08mm (.200") Voided pins, pegs, keys - B-to-B (Board-to-Board) Custom pin lengths, voided pin lengths, voided housings, kinked voided housings, voided header backwall headers, talk, header other options dittion / removal and other options Press-fit pegs - Single Row, Through-Hole Kinked PC tail - Many ways to customize PCB receptacles offered in top, bottom and side entry - Terminals with extra contact points available for IDT (Insulation Displacement Technology) available in feed-to and feed-through high pressure, high 3.96mm (.156") 18-26 AWG vibration environments 2 to 24 7.04 / 13.0A 18-26 AWG 18-26 AWG W-to-B, B-to-B 45570 for 2.54mm (.100") 5.0 A 250V 22-30 AWG 22-30 AWG 101 22-30 AWG W-to-B, B-to-B, 101 W-to-B, B-to-B, receptacles P-to-B, B-to-B, receptacles Headers and pCB receptacles Headers and stockable Circuit Size Virtent Per Pin wire Gouge (AWG) one company > a world of innovation