



- NOTE
- MATERIAL
 - HEADER : LIQUID CRYSTAL POLYMER(LCP) UL94V-0, HALOGEN FREE, COLOR OF NATURAL
 - CONTACT TERMINAL : COPPER-ALLOY, 0.3mm THICKNESS
 - PLATING
 - CONTACT TERMINAL : TIN -PLATED
 - 1.0μm MINIMUM TIN PLATING
 - PRODUCT SPECIFICATION : PS-104188-001
 - PACKAGING SPECIFICATION : PK-104188-001
 - COPLANALITY OF SOLDER TAILS (PEAK TEMP. : 260°C), BEFORE & AFTER REFLOW : 0.08 MAX.
 - APPLICABLE SOLIDE WIRE RANGE : AWG 24~18 (OUTSIDE WIRE INSULATION : 2.1mm DIAMETER MAX.)

PRE-RELEASE
REFERENCE
USE ONLY

PRELIMINARY EC NO: DRWN:JSSHIN CHKD: APPR:	DESCRIPTION 2013/10/14	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 7/1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
		▽=0 ◻=0	4 PLACES	±	±	DRAWN BY JS.SHIN	DATE 2013/08/29	TITLE S-POKE CONNECTOR HEADER ASS'Y -2P			
	3 PLACES	±	±	CHECKED BY SH.CHU	DATE 2013/08/29						
			2 PLACES	± 0.15	±	APPROVED BY	DATE				
			1 PLACE	± 0.20	±	YS00.KIM	2013/08/29				
			0 PLACE	±	±	MATERIAL NO. 1041880210		DOCUMENT NO. SD-104188-003		SHEET NO. 1 OF 1	
			ANGULAR ± 1 °			SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS								