

MITSUBISHI ELECTRIC CORPORATION

APPLICATION NOTE	Prepared by	H.Hanada	Rev	B	H. Hanada.
	Approved by	M.Tabata 1-Apr.-'03			T. Furumi 27-May-'03

CMH5343 b.doc

Subject Performance Curves of CM600DY-24A

Contents


- Output Characteristics(typical)
- Collector-Emitter Saturation Voltage Characteristics(typical)
- Collector-Emitter Saturation Voltage Characteristics(typical)
- Free-Wheel Diode Forward Characteristics(typical)
- Capacitance-VCE Characteristics(typical)
- Half-Bridge Switching Characteristics(typical)
- Reverse Recovery Characteristics of Free-Wheel Diode(typical)
- Transient Thermal Impedance Characteristics(IGBT part&FWDi part)
- Gate Charge Characteristics(typical)

Don't measure these static characteristics yourself by curve tracer.
 Usually, curve tracer has too much wiring inductance and device will be damaged by over voltage from oscillation.

IGBT Module	CMH-5343-B	APPLICATION NOTE
-------------	------------	------------------


APPLICATION NOTE	Prepared by		Rev	
	Approved by			

Output Characteristics (Typical) CM600DY-24A




APPLICATION NOTE	Prepared by		Rev	
	Approved by			

Collector-Emitter Saturation Voltage Characteristics (Typical) CM600DY-24A




APPLICATION NOTE	Prepared by		Rev	
	Approved by			

Collector-Emitter Saturation Voltage Characteristics (Typical) CM600DY-24A




APPLICATION NOTE	Prepared by		Rev	
	Approved by			

Free-Wheel Diode Forward Characteristics (typical) CM600DY-24A




APPLICATION NOTE	Prepared by		Rev	
	Approved by			

Capacitance- V_{CE} Characteristics
(typical)
CM600DY-24A



APPLICATION NOTE	Prepared by		Rev	
	Approved by			


Half-Bridge Switching Characteristics (typical) CM600DY-24A



A

APPLICATION NOTE	Prepared by		Rev	
	Approved by			


Reverse Recovery Characteristics
of Free-Wheel Diode
(typical)
CM600DY-24A



A

APPLICATION NOTE	Prepared by		Rev	
	Approved by			

Transient Thermal Impedance Characteristics (IGBT part & FWD part) CM600DY-24A



IGBT part :

Per unit base= $R_{th(j-c)} = 0.034^\circ\text{C/W}$

FWD part :

Per unit base= $R_{th(j-c)} = 0.062^\circ\text{C/W}$

B

APPLICATION NOTE	Prepared by		Rev	
	Approved by			

Gate Charge Characteristics (typical) CM600DY-24A

