

PRELIMINARY

PM75RLB060

FLAT-BASE TYPE
INSULATED PACKAGE

Notice : This is not a final specification. Some parametric limits are subject to change.

PM75RLB060

Pre. T.Marumo

Rev. A

Apr. M.Yamamoto July.26.2002

T.Marumo
M.Takata 12-Dec.-02

Feature

- a) Adopting new 5th generation IGBT(CSTBT) chip, which performance is improved by $1\mu\text{m}$ fine rule process.

For example, typical $V_{ce}(\text{sat})=1.5\text{V}$ @ $T_j=125^\circ\text{C}$

- b) I adopt the over-temperature conservation by T_j detection of CSTBT chip, and error output is possible from all each conservation upper and lower arm of IPM.

- c) New small package

Reduce the package size by 32%, thickness by 22% from S-DASH series.

- d) Current rating of brake part increased.


67% for the current rating of inverter part.

- 3 ϕ 75A, 600V Current-sense IGBT type inverter
- 50A, 600V Current-sense regenerative brake IGBT
- Monolithic gate drive & protection logic
- Detection, protection & status indication circuits for, short-circuit, over-temperature & under-voltage (P-Fo available from upper arm devices)
- Acoustic noise-less 5.5kW/7.5kW class inverter application

OUTLINE DRAWING Dimensions in mm

See Page 7

APPLICATION : General purpose inverter, servo drives and other motor controls



Maximum Ratings ($T_j = 25^\circ\text{C}$, unless otherwise noted)

Inverter Part

Item	Symbol	Condition	Ratings	Unit
Collector-Emitter Voltage	V_{CES}	$V_D = 15\text{V}, V_{CIN} = 15\text{V}$	600	V
Collector Current	$\pm I_C$	$T_c = 25^\circ\text{C}$	75	A
Collector Current (Peak)	$\pm I_{CP}$	$T_c = 25^\circ\text{C}$	150	A
Collector Dissipation	P_C	$T_c = 25^\circ\text{C}$	(Note-1) 297	W
Junction Temperature	T_j		-20 ~ +150	°C

Brake Part


Item	Symbol	Condition	Ratings	Unit
Collector Emitter Voltage	V_{CES}	$V_D = 15\text{V}, V_{CIN} = 15\text{V}$	600	V
Collector Current	I_C	$T_c = 25^\circ\text{C}$	50	A
Collector Current (Peak)	I_{CP}	$T_c = 25^\circ\text{C}$	100	A
Collector Dissipation	P_C	$T_c = 25^\circ\text{C}$	(Note-1) 228	W
FWDi Rated DC Reverse Voltage	$V_{R(DC)}$	$T_c = 25^\circ\text{C}$	600	V
FWDi Forward Current	I_F	$T_c = 25^\circ\text{C}$	50	A
Junction Temperature	T_j		-20 ~ +150	°C

Control Part

Item	Symbol	Condition	Rating	Unit
Supply Voltage	V_D	Applied between : $V_{UP1}\text{-}V_{UPC}$ $V_{VP1}\text{-}V_{VPC}$, $V_{WP1}\text{-}V_{WPC}$, $V_{N1}\text{-}V_{NC}$	20	V
Input Voltage	V_{CIN}	Applied between : $U_P\text{-}V_{UPC}$, $V_P\text{-}V_{VPC}$ $W_P\text{-}V_{WPC}$, $U_N\text{-}V_N$, $W_N\text{-}B_r\text{-}V_{NC}$	20	V
Fault Output Supply Voltage	V_{FO}	Applied between : $U_{FO}\text{-}V_{UPC}$, $V_{FO}\text{-}V_{VPC}$ $W_{FO}\text{-}V_{WPC}$, $F_O\text{-}V_{NC}$	20	V
Fault Output Current	I_{FO}	Sink current at U_{FO} , V_{FO} , W_{FO} , F_O terminals	20	mA

Total System

Item	Symbol	Condition	Rating	Unit
Supply Voltage Protected by SC	$V_{CC(\text{PROT})}$	$V_D = 13.5\sim 16.5\text{V}$ Inverter Part, $T_j = +125^\circ\text{C}$ Start	400	V
Supply Voltage (Surge)	$V_{CC(\text{surge})}$	Applied between : P-N, Surge value	550	V
Module Case Operating Temperature	T_c	(Note-1)	-20 ~ +100	°C
Storage Temperature	T_{stg}		-40 ~ +125	°C
Isolation Voltage	V_{iso}	60Hz, Sinusoidal Charged part to Base, AC 1 min.	2500	Vrms

(Note-1) T_c (base plate) measurement point is below.

Thermal Resistances


Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Junction to case	R _{th(j-e)Q}	Inverter IGBT part (per 1/6) (Note-2)	—	—	0.32*	°C/W
	R _{th(j-e)F}	Inverter FWDi part (per 1/6) (Note-2)	—	—	0.53*	
	R _{th(j-c)Q}	Brake IGBT part (Note-2)	—	—	0.42*	
	R _{th(j-c)F}	Brake FWDi part (Note-2)	—	—	0.71*	
Thermal Resistances	R _{th(j-c)Q}	Inverter IGBT part (per 1/6) (Note-1)	—	—	0.42	°C/W
	R _{th(j-c)F}	Inverter FWDi part (per 1/6) (Note-1)	—	—	0.69	
	R _{th(j-c)Q}	Brake IGBT part (Note-1)	—	—	0.55	
	R _{th(j-c)F}	Brake FWDi part (Note-1)	—	—	0.92	
Contact Thermal Resistance	R _{th(c-f)}	Case to fin, (per 1 module) Thermal grease applied (Note-1)	—	—	0.038	

* If you use this value, R_{th(f-a)} should be measured just under the chips.

(Note-2) T_c(under the chip) measurement point is below.

(unit : mm)

arm axis	UP		VP		WP		UN		VN		WN		Br	
	IGBT	FWDi												
X	28.7	28.7	65.2	65.2	85.3	85.3	38.0	38.0	55.4	55.4	75.5	75.5	19.0	23.0
Y	-6.6	0.8	-6.6	2.5	-6.6	2.5	4.6	-4.5	4.6	-4.5	4.6	-4.5	-7.3	6.6

Electrical Characteristics (T_j = 25°C unless otherwise noted)

Inverter Part

Item	Symbol	Condition		Min.	Typ.	Max.	Unit
Collector-Emitter Saturation Voltage	V _{CE(sat)}	V _D = 15V, V _{CIN} = 0V	T _j = 25°C	—	1.6	2.1	V
		I _c = 75A, Pulsed	Fig.1	T _j = 125°C	—	1.5	
FWDi Forward Voltage	V _{EC}	I _c = 75A, V _{CIN} = 15V V _D = 15V	Fig.2	—	2.2	3.3	V
Switching Time	ton	V _D = 15V, V _{CIN} = 0V ↔ 15V V _{CC} = 300V, I _c = 75A T _j = 125°C, Inductive Load	Fig.3	0.5	1.0	2.4	μs
	trr			—	0.2	0.4	
	tc(on)			—	0.4	1.0	
	toff			—	1.2	2.5	
	tc(off)			—	0.5	1.0	
Collector-Emitter Cutoff Current	I _{CES}	V _{CE} = V _{CES}	T _j = 25°C	—	—	1	mA
		V _D = 15V	Fig.4	T _j = 125°C	—	10	

Brake Part

Item	Symbol	Condition		Min.	Typ.	Max.	Unit
Collector-Emitter Saturation Voltage	V _{CE(sat)}	V _D = 15V, V _{CIN} = 0V	T _j = 25°C	—	1.6	2.1	V
		I _c = 50A, Pulsed	Fig.1	T _j = 125°C	—	1.5	
FWDi Forward Voltage	V _{FM}	I _f = 50A	Fig.2	—	2.2	3.3	V
Collector-Emitter Cutoff Current	I _{CES}	V _{CE} = V _{CES}	T _j = 25°C	—	—	1	mA
		V _D = 15V	Fig.4	T _j = 125°C	—	10	

Control Part

Item	Symbol	Condition		Min.	Typ.	Max.	Unit
Circuit Current	I _D	V _D = 15V	V _{N1} -V _{NC}	—	20	30	mA
		V _{CIN} = 15V	V _{XPI} -V _{XPC}	—	5	10	
Input ON Threshold Voltage	V _{th(ON)}	Applied between : U _P -V _{UPC} , V _P -V _{VPC} W _P -V _{WPC} , U _N -V _N -W _N -B _r -V _{NC}		1.2	1.5	1.8	V
Input OFF Threshold Voltage	V _{th(OFF)}			1.7	2.0	2.3	
Short Circuit Trip Level	SC	-20≤T _j ≤125°C	Inverter part	150	—	—	A
		V _D = 15V Fig.5,6	Brake part	100	—	—	
Short Circuit Current Delay Time	t _{off(SC)}	V _D = 15V	Fig.5,6	—	10	—	μs
Over Temperature Protection	OT	Detect T _j of IGBT chip	Trip level	135	145	155	°C
	OTr		Reset level	—	125	—	
Supply Circuit Under-Voltage Protection	UV	-20≤T _j ≤125°C	Trip level	11.5	12.0	12.5	V
	UVr		Reset level	—	12.5	—	
Fault Output Current	I _{FO(H)}	V _D = 15V, V _{CIN} = 15V	—	—	—	0.01	mA
	I _{FO(L)}		(Note-2)	—	10	15	
Minimum Fault Output Pulse Width	t _{FO}	V _D = 15V	(Note-2)	1.0	1.8	—	ms

(Note-2) Fault output is given only when the internal SC, OT & UV protections schemes of either upper or lower arm device operate to protect it.

Mechanical Ratings and characteristics

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Mounting torque	—	Mounting part screw : M 5	2.5	3.0	3.5	N · m
Weight	—	—	—	340	—	g

Recommended Conditions For Use

Item	Symbol	Condition	Recommended value	Unit	
Supply Voltage	V _{CC}	Applied across P-N terminals	≤ 400	V	
Control Supply Voltage	V _D	Applied between : V _{UPI} -V _{UPC} V _{VP1} -V _{VPC} , V _{WP1} -V _{WPC} , V _{N1} -V _{NC} (Note-3)	15.0±1.5	V	
Input ON Voltage	V _{CIN(ON)}	Applied between : U _P -V _{UPC} , V _P -V _{VPC}	≤ 0.8	V	
Input OFF Voltage	V _{CIN(OFF)}	W _P -V _{WPC} , U _N -V _N -W _N -B _r -V _{NC}	≥ 9.0		
PWM Input Frequency	f _{PWM}	Using Application Circuit of Fig.8	≤ 20	kHz	
Arm Shoot-through Blocking Time	t _{dead}	For IPM's each input signals	Fig.7	≥ 2.0	μs

(Note-3) With ripple satisfying the following conditions
dv/dt swing ≤ ±5V/μs, Variation ≤ 2V peak to peak

Precautions for testing

- Before applying any control supply voltage (V_D), the input terminals should be pulled up by resistors, etc. to their corresponding supply voltage and each input signal should be kept off state. After this, the specified ON and OFF level setting for each input signal should be done.
- When performing "SC" tests, the turn-off surge voltage spike at the corresponding protection operation should not be allowed to rise above V_{CES} rating of the device.
(These test should not be done by using a curve tracer or its equivalent.)




Fig.1 VCE(sat) Tset




Fig.2 VEC,(VFM) Tset






Fig.3 Switching time test circuit and waveform




Fig.4 ICES Test




Fig.5 SC Test




Fig.6 SC Test waveform

IPM' input signal V_{CIN}
(Upper Arm)

0 V

1.5V

IPM' input signal V_{CIN}
(Lower Arm)

0 V

2V

2V

1.5V

t

t_{dead}t_{dead}

t

1.5V: Input on threshold voltage $V_{th(on)}$ typical value, 2V: Input off threshold voltage $V_{th(off)}$ typical value

Fig.7 Dead time measurement point example





Fig. 8 Application Example Circuit

Notes for stable and safe operation :

- Design the PCB pattern to minimize wiring length between opto-coupler and IPM's input terminal, and also to minimize the stray capacity between the input and output wirings of opto-coupler.
- Connect low impedance capacitor between the Vcc and GND terminal of each fast switching opto-coupler.
- Fast switching opto-couplers : $t_{PLH}, t_{PHL} \leq 0.8 \mu s$, Use High CMR type.
- Slow switching opto-coupler : $CTR > 100\%$
- Use 4 isolated control power supplies (V_D). Also, care should be taken to minimize the instantaneous voltage change of the power supply.
- Make inductance of DC bus line as small as possible, and minimize surge voltage using snubber capacitor between P and N terminal.
- Use line noise filter capacitor (ex. 4.7nF) between each input AC line and ground to reject common mode noise from AC line and improve noise immunity of the system.

Outline drawings

[Dimensions in mm]



Terminal code

- | | | | |
|---------|---------|----------|--------|
| 1. VUPC | 6. VFO | 11. WP | 16. UN |
| 2. UFO | 7. VP | 12. VWP1 | 17. VN |
| 3. UP | 8. VVP1 | 13. VNC | 18. WN |
| 4. VUP1 | 9. VWPC | 14. VN1 | 19. Fo |
| 5. VVPC | 10. WFO | 15. Br | |