

## Features

1. Small size, light weight, high reliability.

2. Low noise, overload protection up to safety standard.

Application	Input Voltage	Output Voltage	Safety Standard	EMI Standard	Remarks
SOHO Equipment	115V AC	5V 0.3A / 24V 4.5A (PEAK) 24V 1.0A (RATE)	Facsimile voluntary	VCCI, FCC	Models which provide a power-saving standby mode are also available.
	230V AC		standard, UL, CSA		
			IEC	VDE, CISPR	
Communication Equipment	115V AC	3.3V 0.2A / 5V 0.6A /	UL, CSA	VCCI, FCC	
	230V AC	9V 0.9A / 15V 0.2A /	IEC	VDE, CISPR	
		25V 0.05A / -27V 0.05A			
Audio Visual Equipment	115V AC	3.3V 1A/5V 1.5A/	UL, CSA	VCCI, FCC	
	230V AC	9V 0.6A / 15V 0.3A /	IEC	VDE, CISPR	
		25V 0.05A / -30V 0.05A			
LCD TV	100V/115V/ 230V AC	24V 7.5A (for 37 inch)	UL, CSA, IEC	VCCI, FCC, CISPR	• W/W input type is available. Models which provide a power-saving standby mode are also available.
		30V / 15V / 10V			
		6V / 5V (Total 70W)			
For High-inch LCD Panel	100/ 115V AC/ 230V	24V 20A	Electrical Appliance and Materials Safety Law of Japan, UL, CSA, IEC	VCCI, FCC, VDE, CISPR	
		15V 4A			
		5V 0.3A			

Continued on the following page.

Continued from the preceding page.

Application	Input Voltage	Output Voltage	Safety Standard	EMI Standard	Remarks
РВХ	115V/ 230V AC	5V 5.0A 12V 1.0A -48V 2.5A	UL, IEC	FCC, CISPR	Provided with Pb battery charging function.
Cell Stations	100V AC	7.2V 1.3A	Electrical Appliance and Materials Safety Law of Japan	VCCI	Provided with Ni-Cd battery charging function.
LCD Projector	100V/120V/ 230V	17V 0.8A / 13V 1.6A / 5V 1.6A / 360V 0.47A	Electrical Appliance and Materials Safety Law of Japan, UL	VCCI, FCC	• Each system like LCD,DLP is available.
			IEC	CISPR	
LED Lighting	100/200V AC	10W (Constant current output) Output 10 to 24V	Electrical Appliance and Materials Safety Law of Japan	VCCI	PWM Dimming, Accepted for triac dimming
		80W (Constant current output) Output 30V			