

Weight Indicator



FEATURES

- Economical general-purpose weighing indicator
- Large 6 digit LED display
- Two serial ports for simultaneous printer and PC connection
- Heavy duty ABS enclosure
- Sample rate up to 30 conversions per second
- OIML R-76 and NTEP approved to 10000d
- 3 level digital filtering
- Programmable ticket format up to 185 characters
- Consecutive transaction numbering

NOT AVAILABLE IN THE FOLLOWING REGIONS:

North America, Central America, South America

DESCRIPTION

The VT 100 is an economical general purpose weighing indicator for platform scales and other industrial applications.

Two serial ports, RS-232 and current loop, provide simultaneously PC and printer interface capability. Ticket formats may be edited and downloaded with programmable ticket numbering, date, and time.

Load cells are connected using a quick disconnect plug, allowing simple installation and maintenance.

The heavy duty ABS enclosure easily adjusts for desktop, wall (tilt), or post mounting.

APPLICATIONS

- Shipping and receiving scales
- Floor scales
- Bench scales

CONFIGURATION



OPTIONS

- UL power adaptor
- TUV power adapter
- UK power adapter
- High tilt stand
- Low tilt stand

Weight Indicator

SPECIFICATIONS

PERFORMANCE

Resolution:	10000 or 100000 dd (selectable)
Conversion Speed:	3, 7, 15, or 30 samples (selectable)
Sensitivity:	1.0 μ V/Vsi for approved scales, 0.5 μ V/Vsi for non-approved scales.
Full Scale Range:	3mV/V
Linearity:	0.01% of full scale
Long Term Stability:	0.005% of full scale per year
Excitation:	+5VDC with sense (6 wires)
Number of Cells:	Up to 8, 350 ohm load cells
Filter:	digital filter - 3 stages
Offset Drift:	3.5ppm/ $^{\circ}$ C
Span Drift :	3.5ppm/ $^{\circ}$ C
A/D Converter Type:	Sigma-Delta, ratiometric
Count By:	x1, x2, x5, x10, x50
Decimal Point:	between any digits of the weight display
Calibration Methods:	dead load and span, store in EEPROM
Weighing Functions:	automatic zero tracking, motion detection, auto-zero on power-up, zero, tare, gross/net, print, units conversion

ENVIRONMENTAL

Operating Temp:	-10 $^{\circ}$ C to +40 $^{\circ}$ C [14 $^{\circ}$ F to 104 $^{\circ}$ F]
Storage Temp:	-10 $^{\circ}$ C to +70 $^{\circ}$ C [-4 $^{\circ}$ F to 158 $^{\circ}$ F]
Relative Humidity:	40-90% RH, non-condensing

DISPLAY AND KEYBOARD

Display:	6 digit, 7-segment, LED, 20.3mm
Status Enunciators:	no motion, zero, net, units (kg, g)
Weight Digits:	4, 5 or 6 (setup selectable)
Keyboard:	5 key membrane keyboard, with tactile feedback

ELECTRICAL

Voltage:	9VDC or 115 or 230VAC using power adapter
Power:	8W

SERIAL COMMUNICATION

Serial Output #1:	RS-232
Baud Rate:	1200 - 38400 baud, full duplex
Applications:	continuous or printer output, PC interface
Serial Output #2:	20mA current loop - output only
Baud Rate:	1200 - 9600 baud
Applications:	printer port

ENCLOSURE

Heavy Gage ABS:	
Dimensions:	186.3x103x95mm LxHxD [7.32x4.05x3.74in. LxHxD]
Mounting:	desktop, wall and tilt mount

APPROVALS (ACCURACY CLASS III)

OIML R-76:	10000d EU-type approval no. T6877
NTEP:	10000d single interval

Transducers is continually seeking to improve product quality and performance. Specifications may change accordingly.

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay Precision Group disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.